



Dimension board

LENGTH	1200 mm
WIDTH	165 mm
TOTAL THICKNESS	9.5 mm
THICKNESS TOP LAYER	1 mm
LAYER CONTENTS	Min 10 Pl x 1200 mm

Dimension pack

PACK LENGTH	1250 mm
PACK WIDTH	175 mm
PACK THICKNESS	125 mm
PACK WEIGHT	21 kg
LAYERS/BOX	13
M²/PACK	2.57 m ²

Dimension pallet

PALLET LENGTH	1250 mm
PALLET WIDTH	1050 mm
PALLET HEIGHT	1100 mm
PALLET WEIGHT	1000 kg
PACKS/PALLET	48
M²/PALLET	123.36 m ²

CHARACTERISTICS

Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	CLASSIC
CONSTRUCTION	3-layer
THICKNESS TOP LAYER	1 mm
PATTERN	1 strip
CUTTING METHOD	Zaagfineer
BEVEL	Micro bevel 4 sides
FINISH	Lacquer
SURFACE STRUCTURE	Smooth

Composition of the support

SUPPORT TYPE	HDF
WOOD SPECIES SUPPORT	Berk
TOTAL THICKNESS SUPPORT	8 mm
ADHESION	Kruiselings

Installation

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Click	Light household use. Moderate commercial use. Normal commercial use. Normal household use. Intensive commercial use.	Yes RE-SANDABLE No

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m ² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION

