



Dimension board

LENGTH	2200 mm
WIDTH	220 mm
TOTAL THICKNESS	14.0 mm
THICKNESS TOP LAYER	4 mm
LAYER CONTENTS	Min 2 Pl x 1800 mm

Dimension pack

PACK LENGTH	2250 mm
PACK WIDTH	225 mm
PACK THICKNESS	84 mm
PACK WEIGHT	31 kg
LAYERS/BOX	6
M²/PACK	2.90 m ²

Dimension pallet

PALLET LENGTH	2250 mm
PALLET WIDTH	90 mm
PALLET HEIGHT	1100 mm
PALLET WEIGHT	1342 kg
PACKS/PALLET	44
M²/PALLET	127.60 m ²

CHARACTERISTICS

Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	ABCD
CONSTRUCTION	2-layer
THICKNESS TOP LAYER	4 mm
PATTERN	1 strip
CUTTING METHOD	Zaagfineer
BEVEL	Bevel 2 long sides 0,75 mm
FINISH	Onbehandeld
SURFACE STRUCTURE	Smooth

Composition of the support

SUPPORT TYPE	MPX
WOOD SPECIES SUPPORT	Mixed Light Hardwood
TOTAL THICKNESS SUPPORT	10 mm
ADHESION	Kruiselings

Installation

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	Light household use. Moderate commercial use. Normal commercial use. Normal household use. Intensive commercial use.	Yes RE-SANDABLE Yes

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m ² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION



EN 14342

