

CAMPAGNE - SOLID WOOD - BRUT A14424



LENGTH	2200 mm
WIDTH	180 mm
TOTAL THICKNESS	20.0 mm

Dimension	nack

PACK LENGTH	2250 mm
PACK WIDTH	185 mm
PACK THICKNESS	105 mm
PACK WEIGHT	29 kg
LAYERS/BOX	5
M ² /PACK	1 98 m²

Dimension pallet

PALLET LENGTH	2250 mm
PALLET WIDTH	925 mm
PALLET HEIGHT	875 mm
PALLET WEIGHT	1305 kg
PACKS/PALLET	45
M ² /PALLET	89.10 m ²

CHARACTERISTICS

10	D	lav	9

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	CLASSIC B
PATTERN	1 strip
BEVEL	Micro bevel 4 sides
FINISH	Onbehandeld
SURFACE STRUCTURE	Smooth

Composition of the support

SUPPORT TYPE	Massief hout
0011 OK1 111 E	171033101 11001

Installation

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	Light household use.	No
	Moderate commercial use.	
	Normal commercial use. RE-SANDABLE	RE-SANDABLE
	Normal household use.	No
	Intensive commercial use.	

[©] This fact sheet was written by Labeco BVBA, Sprietestraat 326, B-8792 Waregem. Text, photographs, drawings, tables, graphs should in no way be distributed, used or copied unless LABECO BVBA has granted reproduction rights. At the moment of establishment of the sheet, all information is specified correctly. The company reserves the right to change the specifications of the product at any time without prior notice to third parties. The photographs, drawings, tables, graphs used in this sheet are intended only as illustrations. No rights can be derived from them.



CAMPAGNE - SOLID WOOD - BRUT

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION









