



Dimension board

LENGTH	2130 mm
WIDTH	240 mm
TOTAL THICKNESS	14.0 mm
THICKNESS TOP LAYER	3 mm
LAYER	5 pl x 2130 mm + 2 pl
CONTENTS	RL 600-2130 mm

Dimension pack

PACK LENGTH	2140 mm
PACK WIDTH	245 mm
PACK THICKNESS	86 mm
PACK WEIGHT	31 kg
LAYERS/BOX	6
M ² /PACK	3.07 m ²

Dimension pallet

PALLET LENGTH	2140 mm
PALLET WIDTH	740 mm
PALLET HEIGHT	1050 mm
PALLET WEIGHT	1050 kg
PACKS/PALLET	33
M ² /PALLET	101.31 m ²

CHARACTERISTICS

Top layer

WOOD SPECIES	Oak
LATIN NAME	Quercus Robur
GRADE	CLASSIC A
CONSTRUCTION	3-layer
THICKNESS TOP LAYER	3 mm
PATTERN	1 strip
CUTTING METHOD	Zaagfineer
BEVEL	Micro bevel 2 long sides
FINISH	Lacquer
SURFACE STRUCTURE	Smooth

Composition of the support

SUPPORT TYPE	Hevea
WOOD SPECIES SUPPORT	Hevea
TOTAL THICKNESS SUPPORT	11 mm
ADHESION	Kruiselings

Installation

SYSTEM	APPLICATIONS	UNDERFLOOR HEATING
Tongue and groove	Light household use.	Yes
	Moderate commercial use.	
	Normal commercial use.	RE-SANDABLE
	Normal household use.	Yes
	Intensive commercial use.	

TECHNICAL SPECIFICATIONS

	Norm	Result
REACTION TO FIRE	EN 13501-1	Dfl-S1
FORMALDEHYDE EMISSION	EN 717-1	E1
PCP	CEN/TR 14823	≤ 5ppm
THERMAL CONDUCTIVITY	EN 12667 / ISO 8302	0,11m ² k/w
BIOLOGICAL DURABILITY	EN 335	Class 1
BREAKING STRENGTH	EN 1533	Pass
SLIPPERINESS	EN 15676	Pass
MOISTURE CONTENT	EN 13183-1	7% (+/-2%)

CERTIFICATION



EN 14342

